



The Right Connection®

Data Sheet

Reusable Fittings



Reusable Fittings

180	Ferrule
180-SS	Ferrule - Stainless Steel
182	Male Stem
182-SS	Male Stem- Stainless Steel
183	Reusable Set - Ferrule and Male Stem
183-SS	Reusable Set - Ferrule and Male Stem Stainless Steel
184	Female Swivel Stem
185	Reusable Set - Ferrule and Female Swivel Stem
186	Hose Splicer
187	Hose Splicer Set (ferrules and splicer)

Compatible Hoses:

- Low Pressure Rubber Covered Hose only for air and water service

Materials:

- Brass: Alloy 360
- Stainless Steel: Alloy 303 SS

Performance:

- Working pressure: 250 PSI at ambient temperature (72°F)
- Operating temperature range: -40°F to 160°F at 150 PSI
- Vacuum: not rated

Applications / Markets:

- Industrial air and non-potable water service
- Used when a more durable hose connection is required
- Ease of making a repair is a major consideration

Strengths / Features:

- Over 110 re-usable fittings in male thread, female thread or splicer combinations
- Fittings are of heavy duty construction
- Used for field repair

Dixon Brass

ph 800.323.4440

fx 800.628.7259

customer.service@dixonbrass.com

dixonvalve.com