

Unloader Valves

Features

- Automatically relieves pressure from the pump at shut-off
- Inlet: (2) each, 3/8" female NPT
- Outlet: 3/8" female NPT
- Bypass: (2) each, 3/8" female NPT

Specification

- Maximum temperature: 190°F (88°C)

Description	Maximum Flow (GPM)	Working PSI	Part #
yellow spring	8	2,320	AL605
blue spring	8	3,650	AL606
black spring	8	4,500	AL607



Features

- Inlet: 3/8" female
- Outlet: 3/8" male
- Bypass: 3/8" female

Specification

- Maximum temperature: 190°F (88°C)

Description	Flow (GPM)	Working PSI	Part #
VR-35 unloader valve	9	5,100	AR20831



Thermal Relief Valve

Features

- Inlet: 1/2" male

Specifications

- Operating PSI: 200 PSI
- Maximum temperature: 140°F (60°C)

Brass
Part #

TPP140



Safety Release Valve

Features

- Inlet: 3/8" male

Specifications

- Pressure range: 1,000 to 4,000 PSI
- Maximum temperature: 200°F (93°C)
- GPM: 6

Part #

AR5000-1



Pressure Washer Braided Hose

Specification

- Maximum temperature: 250°F (121°C)

I.D.	Male Swivel Inlet	Male Swivel Outlet	Pressure Rating (PSI)	Length	Rubber Part #
3/8"	3/8"	3/8"	4,000	50'	AR503830SSP



Hand Crank Hose Reel

Features

- 3/8" outlet, 3/8" inlet
- Includes jumper hose, mounting bracket and crank handle
- Holds 100' of 3/8" pressure hose

Specifications

- Working PSI: 3,000 PSI
- Maximum temperature: 160°F (71°C)

Steel
Part #

AR-REEL100

