

Dixon™ 2-Way Ball Valves

Features:

- valve feeds two smaller attack lines from one large diameter supply line, 2½" outlet is a gated ball valve providing a safe controlled flow of water
- compact valve comes standard with a carrying handle
- maximum operating pressure: **280 PSI** at 70°F (21°C), without relief valve
- water way: inlet side - 4½" maximum, 2 outlets - 2½" maximum
- finish anodized throughout - minimum thickness 0.001"
- available with Storz or threaded combinations
- can be used to distribute water in the opposite direction

Inlet Storz	Outlet Male	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
2½"	2½"	MSBV2525F	\$1918.55	9"	8"	7"
3"	2½"	MSBV325F	1871.25	9"	8½"	7"
4"	2½"	MSBV425F	1718.20	12"	9¾"	9"
5"	2½"	MSBV525F	1837.80	12½"	9¾"	9"
6"	2½"	MSBV625F	2061.85	12½"	10¼"	9"

Storz Inlet with (2) Outlets

Inlet Storz	(2) Outlet Storz	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
2½"	2½"	SBV2525	\$1888.45	9"	8"	7"
3"	2½"	SBV325	1872.65	9"	8½"	7"
4"	2½"	SBV425	1858.10	12"	9¾"	9"
5"	2½"	SBV525	1983.50	12½"	12"	9"
6"	2½"	SBV625	1726.50	12½"	12"	9"

Inlet Storz	(2) Outlet Female	Alum. Alloy, 356-T6 Part #	Price	Length	Width	Height
2½"	2½"	FSBV2525F	\$1986.95	9"	8"	7"
3"	2½"	FSBV325F	1971.20	9"	8½"	7"
4"	2½"	FSBV425F	1922.50	12"	11½"	9"
5"	2½"	FSBV525F	2047.85	12½"	11½"	9"
6"	2½"	FSBV625F	1756.65	12½"	12"	9"

- all measurements include handles

