Constant Flow
Nozzles

BUILT TOUGH TO WITHSTAND THE ELEMENTS

The Right Connection®

Constant Flow Nozzle Displays

Application
- Shatter-resistant and UV-resistant polycarbonate is able to withstand tough environmental conditions

Features
- Seals used for true water shut off
- Easy twist spray pattern adjustment
- Sold in case quantity only (25 per case), with display

GHT Thread	45° Spray GPM @ 100 PSI	Color	Required Case Qty	Part #
3/4"	**25.1**	clear	1	CNB75GHT-GD
3/4"	**25.1**	green	1	FNB75GHT-GD

Constant Flow Nozzles with Bumper

Feature
- Can be used as a replacement nozzle in the display case FNB75GHT-GD

Domestic

GHT Thread	45° Spray GPM @ 100 PSI	Color	Part #
3/4"	**8**	green	GNB75GHT

Global

GHT Thread	45° Spray GPM @ 100 PSI	Color	Part #
3/4"	**25.1**	clear	CNB75GHT
		green	FNB75GHT-G
		red	FNB75GHT

GNB75GHT

CNB75GHT

FNB75GHT-G

FNB75GHT

© 2024 DVCC • DPproductdisplay_324

Dixon Fire

325 Arbor Ct
Winchester, VA 22602
ph: 877.712.6179
fx: 800.283.4966
dixonvalve.com